
Offshore Farming

Shackles





- Material:
- Body and pin high tensile steel, quenched and tempered. • Safety factor: 6 times WLL (Working Load Limit) = minimum breaking strength.
- Finished: Galvanized.
- Standard:

Meets performance requirement of U.S. Federal Specification RR-C-271.

We supply anchor shackle ("Bow" type) with screw collar pin or bolttype, and safety chain shackle ("Dee" type) with screw collar pin or bolt type.

Shackles in use should be subject to thorough examination by a competent person at least every six months.

Finished shackles may not be heat-treated because this may affect the WLL and the material structure. Avoid applications where due to movement the shackle pin can rotate and possibly be unscrewed.

WLL	Ø Bow	Ø pin	Inside	width	Inside length		Width	Approx. weight / shackle			
			shackles		shackles		of bow	Bow		Dee	
		1						Screw	Safety	Screw	Safety
		-	Bow	Dee	Bow	Dee		pin	pin	pin	pin
tons	mm	mm	mm	mm	mm	mm	mm	kg	kg	kg	kg
4,75	19	22	32	31	76	59	51	1,01	1,18	0,87	1,08
6,5	22	25	36,5	36	83	73	58	1,50	1,77	1,34	1,66
8,5	25	28	43	43	95	85	68	2,21	2,58	2,08	2,46
9,5	28	32	46	47	108	90	75	3,16	3,66	2,77	3,40
12	32	35	51,5	51	115	94	83	4,31	4,91	3,72	4,51
13,5	35	38	57	57	133	115	92	5,55	6,54	5,14	6,10
17	38	42	60	60	146	127	99	7,43	8,19	6,85	7,63
25	45	50	73	74	178	149	126	12,84	14,22	11,45	13,25

Anchors

Anchors:

The anchor is the symbol of the hope. Various anchor types are available (Plough, Delta flipper, Danforth, etc.). Please specify your needs and we will make an offer.





Various anchor types are available.

Chains, cables:

Various types can be delivered such as, galvanized steel chain, alloy steel chain, short link chain, long link chain, high grade alloy steel chain, etc. Please specify your needs and we will make an offer.



Various cables and chains types are available.



Catvis

K Q An IChC